

## TP610



### Application range

This high-end joint sealing tape is used for the external driving rain-proof sealing of connection joints in building construction. TP610 is used in window installation, metal, wood and container construction.

Open-cell flexible polyurethane foam with polymer impregnate. Solvent-free single-sided self-adhesive to aid assembly. TP610 is manufactured without halogen-containing flame retardants, solvent-free and without using (H)CFC/CFCS.

### Properties

- > Impervious to driving rain 600 Pa and weather resistant with BG1 test
- > Vapor diffusible for drying out the joint
- > Wide range of dimension in two colours
- > EC1 PLUS and DGNB certified
- > For economical RAL quality-assured window installation
- > TP610 is supplied as compressed roll material, with one-sided self-adhesion in grey

### Note

Weigh down residual rolls in opened cartons to avoid lateral opening (telescoping) of the rolls. The tape can be plastered and painted over. Compatibility should be tested when coating with light colors and sealants (white and transparent). The tape must not be exposed to or cleaned with solvent-based or aggressive chemicals. Sealing tape must be stored in a dry place until installation.

### Technical specifications



### Product online



Order description	Band width* [mm]	Application range [mm]	Roll length total [m]	Content roll [pieces]	PU [m]	Price/100 m [EUR]	Article number	EAN
TP 610 10 / 1-2 anthracite	10	1–2	12.5	11	137.5		0061010102	4025109372106
TP 610 10 / 2-4 anthracite	10	2–4	10.0	11	110.0		0061010204	4025109373103
TP 610 12 / 3-6 anthracite	10	3–6	8.0	9	72.0		0061012306	4025109081695
TP 610 15 / 1-2 anthracite	15	1–2	12.5	7	87.5		0061015102	4025109372151
TP 610 15 / 2-4 anthracite	15	2–4	10.0	7	70.0		0061015204	4025109373158
TP 610 15 / 3-6 anthracite	15	3–6	8.0	7	56.0		0061015306	4025109374155
TP 610 15 / 4-10 anthracite	15	4–10	5.6	7	39.2		0061015410	4025109276152
TP 610 15 / 5-12 anthracite	15	5–12	4.3	7	30.1		0061015512	4025109378153
TP 610 20 / 1-2 anthracite	20	1–2	12.5	5	62.5		0061020102	4025109011791
TP 610 20 / 2-4 anthracite	20	2–4	10.0	5	50.0		0061020204	4025109090758
TP 610 20 / 3-6 anthracite	20	3–6	8.0	5	40.0		0061020306	4025109374209
TP 610 20 / 4-10 anthracite	20	4–10	5.6	5	28.0		0061020410	4025109376203
TP 610 20 / 5-12 anthracite	20	5–12	4.3	5	21.5		0061020512	4025109378207

**\*Dimensional tolerances according to DIN7715 P3**