

Installation tool ECOset HTK



Application range

> For safe, fast and efficient installation of EJOT® HTK 2G stress plates with EJOT DABO® screws TKR, TKE and VHT-R

Characteristics

- > Variable length combinations with fast and direct locking adjustment
- > HTK collator change in seconds (25 pcs. pre-collated)
- > Due to the depth stop, screws can not be overwound

Advantages

- > Short assembly times with pre-collated fasteners
- Easy and secure lock-in installations for different stress plate lengths
- > Fatigue-free fixing with high degree of installation reliability
- > Insulation thickness max. 280 mm

Notice

HTK 2G stress plates can be processed up to 145 mm in length.

Included in delivery

- 1 1 installation tool (includes screwgun and H2-M6x35 mm bit)
- 1 spare battery
- 1 tool kit
- 1 operating manual

Cross references

Stress plate HTK 2G Bit PH2-1/4"Ex200 Battery packs and chargers

Battery voltage	18 V		
Load speed	0-1500 rpm		
Idle speed	0-1700 rpm		
Max. torque (hard/soft)	30/10 Nm		
Weight	24 kg		

3-year FEIN PLUS Warranty

including battery and charger (if registered online)

Info see page 405

Try now as rental equip-

ment Article number G000000072

Comprehensive equipment and product training at your construction site by the EJOT team

Info see page 33



Cartridge holder

By using the optional cartridge holder, the installation tool ECOSET-HTK can be filled with three cartridge loads at the same time. That equals 75 fasteners.

Product online





Order description	PU [pieces]	Price/1 [EUR]	Article number	EAN
EJOT® installation tool ECOset HTK (18-V drive)	1		9153500000	4061245020303
Accessories				
Bit PH 2 - M6 x 35	1		9250612000	4061245021027
Transport box	1		9151506000	4061245020402
Spray oil 100 ml	1		9150911000	4017777216004
Cartridge holder for ECOset-HTK	1		9151510074	4061245020396
Rapid charger ALG 80	1		9154200008	4014586890630
Battery pack 18V / 6.0 Ah	1		9154200009	4014586890586