



according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. A

Revision date: 29.11.2022 Page 1 of 12

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Multifix SE1000 Seismic, Comp. A

UFI: D0RK-8TG4-2V80-JXMX

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesive mortar for fastening elements A-component (resin)

### Uses advised against

no restriction

#### 1.3. Details of the supplier of the safety data sheet

Company name: EJOT Baubefestigungen GmbH

Geschäftsbereich Building Fasteners

Street: In der Stockwiese 35
Place: D-57334 Bad Laasphe
Telephone: +46 19 20 65 00
e-mail: www.ejot.de

**1.4. Emergency telephone** Medical emergency information in the event of poisoning:

number: Giftinformationszentrum Mainz - 24h - Tel .: +49 (0) 6131 19240 (advice in

German or English)

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

### **GB CLP Regulation**

Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

#### **GB CLP Regulation**

#### Hazard components for labelling

2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane;

1,6-hexanediol diglycidyl ether

Signal word: Warning

**Pictograms:** 





### **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

P264 Wash hands thoroughly after handling.
P273 Avoid release to the environment.



according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. A

Revision date: 29.11.2022 Page 2 of 12

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

#### 2.3. Other hazards

People who are allergic to epoxide should avoid the use of the product.

Use only outdoors or in a well-ventilated area.

### **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

#### **Hazardous components**

CAS No	Chemical name	Chemical name				
	EC No	Index No REACH No				
	Classification (GB CLP Regulat	ion)				
1675-54-3	2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane					
	216-823-5	603-073-00-2 01-2119456619-26				
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411					
933999-84-9	1,6-hexanediol diglycidyl ether					
	618-939-5 01-2119463471-41		01-2119463471-41			
	Skin Irrit. 2, Eye Irrit. 2, Skin Se	ens. 1, Aquatic Chronic 3; H315 F	H319 H317 H412			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits. M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc.	cific Conc. Limits, M-factors and ATE		
1675-54-3	216-823-5	2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	30 - < 60 %	
	dermal: LD50 Irrit. 2; H319:	= 23000 mg/kg; oral: LD50 = 15000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye >= 5 - 100		
933999-84-9	618-939-5	1,6-hexanediol diglycidyl ether	10 - < 15 %	
	dermal: LD50	= > 2000 mg/kg; oral: LD50 = 3010 mg/kg		

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

#### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

#### 4.2. Most important symptoms and effects, both acute and delayed





according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. A

Revision date: 29.11.2022 Page 3 of 12

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam

Extinguishing powder

Water spray jet

Carbon dioxide (CO2)

### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic

Carbon monoxide

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

#### **Additional information**

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

## 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

### Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

### Advice on safe handling

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.



according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. A

Revision date: 29.11.2022 Page 4 of 12

When using do not eat, drink or smoke.

#### Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed.

Store in a place accessible by authorized persons only.

Keep only in the original container in a cool, well-ventilated place.

### Hints on joint storage

Do not store together with: Oxidising agent, strong

Do not use for products which come into contact with the food stuffs.

### Further information on storage conditions

storage temperature: 5 - 35°C

## 7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### **DNEL/DMEL values**

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
933999-84-9	1,6-hexanediol diglycidyl ether					
Worker DNEL	., long-term	inhalation	systemic	10,57 mg/m³		
Worker DNEL	, long-term	inhalation	local	0,44 mg/m³		
Worker DNEL	, long-term	dermal	systemic	6,0 mg/kg bw/day		
Worker DNEL	, long-term	dermal	local	0,0226 mg/cm <sup>2</sup>		
Consumer DN	NEL, long-term	inhalation	systemic	5,29 mg/m³		
Consumer DN	NEL, long-term	inhalation	local	0,27 mg/m³		
Consumer DN	NEL, long-term	dermal	systemic	3,0 mg/kg bw/day		
Consumer DN	NEL, long-term	dermal	local	0,0136 mg/cm <sup>2</sup>		
Consumer DN	IEL, acute	inhalation	systemic	5,29 mg/m³		
Consumer DN	IEL, acute	dermal	systemic	1,7 mg/kg bw/day		
Consumer DNEL, acute		dermal	local	0,0136 mg/cm <sup>2</sup>		
Consumer DNEL, long-term		oral	systemic	1,5 mg/kg bw/day		
Consumer DN	IEL, acute	oral	systemic	1,5 mg/kg bw/day		

#### **PNEC values**

CAS No	Substance				
Environmenta	Environmental compartment Value				
933999-84-9	933999-84-9 1,6-hexanediol diglycidyl ether				
Freshwater 0		0,0115 mg/l			
Marine water		0,00115 mg/l			
Freshwater sediment (		0,283 mg/kg			
Marine sedim	Marine sediment (				



according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. A

Revision date: 29.11.2022 Page 5 of 12

#### Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

#### 8.2. Exposure controls







## Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear eye/face protection. Wear safety glasses.

#### Hand protection

Recommended material: NBR (Nitrile rubber)

Breakthrough time: > 480 min

Thickness of the glove material: 0,7 mm

DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Wear suitable protective clothing.

## Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: solid (pasty)
Colour: light beige
Odour: characteristic
Odour threshold: No data available

#### Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

not determined

not determined

boiling range:

Flash point: not applicable

**Flammability** 

Solid/liquid: not determined
Gas: not applicable

**Explosive properties** 

The product is not: Explosive.

Lower explosion limits: not determined Upper explosion limits: not determined



according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. A

Revision date: 29.11.2022 Page 6 of 12

#### Self-ignition temperature

Solid:
Gas:

Decomposition temperature:

pH-Value:

Not determined not determined not determined not determined

pH-value:

The study does not need to be conducted because the substance is known to be

insoluble in water.

### Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Density (at 20 °C):

Relative vapour density:

not determined

1,45 g/cm³

not determined

#### 9.2. Other information

#### Information with regard to physical hazard classes

Oxidizing properties Not oxidising.

### Other safety characteristics

Solid content: not determined Evaporation rate: not determined

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent, strong

### 10.4. Conditions to avoid

Heat. Keep cool. Protect from sunlight.

### 10.5. Incompatible materials

Keep away from: Oxidizing agent

#### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

### **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in GB CLP Regulation

#### **Acute toxicity**

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. A

Revision date: 29.11.2022 Page 7 of 12

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
1675-54-3	2,2'-[(1-Methylethylider	ne)bis(4,1-pher	nyleneo	xymethylene)]bisoxiran	е		
	oral	LD50 15 mg/kg	5000	Rat			
	dermal	LD50 23 mg/kg	3000	Rabbit			
933999-84-9	1,6-hexanediol diglycid	yl ether					
	oral	LD50 30 mg/kg	)10	Rat			
	dermal	LD50 > 2 mg/kg	2000	Rat		OECD 402	

## Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

#### Sensitising effects

May cause an allergic skin reaction. (2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane; 1,6-hexanediol diglycidyl ether)

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### **Further information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
1675-54-3	2,2'-[(1-Methylethyliden	e)bis(4,1-pl	henyleneox	ymethy	rlene)]bisoxirane		
	Acute fish toxicity	LC50	2 mg/l		Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50	11 mg/l	72 h			
	Acute crustacea toxicity	EC50	1.8 mg/l		Daphnia magna (Big water flea)		
933999-84-9	1,6-hexanediol diglycidy	l ether					
	Acute fish toxicity	LC50	30 mg/l		Oncorhynchus mykiss (Rainbow trout)		
	Acute crustacea toxicity	EC50	47 mg/l		Daphnia magna (Big water flea)		

### 12.2. Persistence and degradability

The product has not been tested.



according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. A

Revision date: 29.11.2022 Page 8 of 12

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation					
933999-84-9	1,6-hexanediol diglycidyl ether					
	OECD 301D	71 %	28			

#### 12.3. Bioaccumulative potential

The product has not been tested.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
933999-84-9	1,6-hexanediol diglycidyl ether	0,822

#### **BCF**

CAS No	Chemical name	BCF	Species	Source
933999-84-9	1,6-hexanediol diglycidyl ether	3,57		

### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No information available.

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

#### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### **Disposal recommendations**

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

### List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

### List of Wastes Code - contaminated packaging



according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. A

Revision date: 29.11.2022 Page 9 of 12

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

## **SECTION 14: Transport information**

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

14.3. Transport hazard class(es):

14.4. Packing group: III Hazard label: 9



Classification code: M7

Special Provisions: 274 335 375 601

Limited quantity: 5 kg
Excepted quantity: E1
Transport category: 3
Hazard No: 90
Tunnel restriction code: -

Other applicable information (land transport)

No dangerous goods in packaging until 5 kg according special instruction 375 ADR/RID

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3077

**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Classification code: M7

Special Provisions: 274 335 375 601

Limited quantity: 5 kg
Excepted quantity: E1

Other applicable information (inland waterways transport)

No dangerous goods in packaging until 5 kg according special instruction 375 ADN

Marine transport (IMDG)

14.1. UN number or ID number: UN 3077

**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Special Provisions: 274, 335, 966, 967, 969

Limited quantity: 5 kg
Excepted quantity: E1





according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. A

Revision date: 29.11.2022 Page 10 of 12

EmS: F-A, S-F
Other applicable information (marine transport)

No dangerous goods in packaging until 5kg according 2.10.2.7 IMDG Code

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Special Provisions: A97 A158 A179 A197 A215

Limited quantity Passenger: 30 kg G
Passenger LQ: Y956
Excepted quantity: E1

IATA-packing instructions - Passenger:956IATA-max. quantity - Passenger:400 kgIATA-packing instructions - Cargo:956IATA-max. quantity - Cargo:400 kg

Other applicable information (air transport)

No dangerous goods in packaging until 5 kg according A197 IATA-DGA

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



### 14.6. Special precautions for user

No information available.

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to 2012/18/EU 
E2 Hazardous to the Aquatic Environment (SEVESO III):

**Additional information** 

VOC content: < 0,1 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juveniles according to the

'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.



according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. A

Revision date: 29.11.2022 Page 11 of 12

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

### Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

BCF: Bioconcentration factor

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level DNEL: Derived No Effect Level EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

ICAO: International Civil Aviation Organization

IC50: Inhibitory concentration, 50%

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Oragnisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations

Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Aquatic Chronic 2: Long-term aquatic hazard, Category 2 Aquatic Chronic 3: Long-term aquatic hazard, Category 3 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2 Skin Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1: Skin sensitilization, Category 1

## Classification for mixtures and used evaluation method according to GB CLP Regulation

	- · · · · · · · · · · · · · · · · · · ·
Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

### Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product





according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. A

Revision date: 29.11.2022 Page 12 of 12

named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)





according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. B

Revision date: 29.11.2022 Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Multifix SE1000 Seismic, Comp. B

UFI: D3RK-ST5H-CV8H-6970

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

compound mortar B-component (hardener)

#### Uses advised against

no restriction

#### 1.3. Details of the supplier of the safety data sheet

Company name: EJOT Baubefestigungen GmbH

Geschäftsbereich Building Fasteners

Street: In der Stockwiese 35
Place: D-57334 Bad Laasphe
Telephone: +46 19 20 65 00
e-mail: www.ejot.de

**1.4. Emergency telephone** Medical emergency information in the event of poisoning:

number: Giftinformationszentrum Mainz - 24h - Tel .: +49 (0) 6131 19240 (advice in

German or English)

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

## **GB CLP Regulation**

Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

#### **GB CLP Regulation**

### Hazard components for labelling

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine;

m-Phenylenebis(methylamine);

2,4,6-Tris(dimethylaminomethyl)phenol

Signal word: Danger

Pictograms:





### **Hazard statements**

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

### **Precautionary statements**

P260 Do not breathe dusts or mists.

P280 Wear protective gloves/protective clothing/eye protection/face protection.



according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. B

Revision date: 29.11.2022 Page 2 of 13

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container to an approved waste disposal plant in accordance with

local/national regulation.

#### 2.3. Other hazards

Contains Amines. May produce an allergic reaction. Use only outdoors or in a well-ventilated area.

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

### **Hazardous components**

CAS No	Chemical name			Quantity		
	EC No	Index No	REACH No			
	Classification (GB CLP Regu	lation)	·			
25513-64-8	2,2,4(or 2,4,4)-Trimethylhexa	ne-1,6-diamine		25 - < 35 %		
	247-063-2		01-2119560598-25			
	Acute Tox. 4, Skin Corr. 1A,	Eye Dam. 1, Skin Sens. 1A;	H302 H314 H318 H317			
1477-55-0	m-Phenylenebis(methylamin	e)		1 - < 8 %		
	216-032-5		01-2119480150-50			
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1B, Aquatic Chronic 3; H332 H302 H314 H318 H317 H412					
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol			5 - < 10 %		
	202-013-9		01-2119560597-27			
	Acute Tox. 4, Skin Corr. 1C, Eye Dam. 1; H302 H314 H318					
104-15-4	p-Toluenesulphonic acid			1 - < 5 %		
	203-180-0	016-030-00-2	01-2119538811-39			
	Skin Irrit. 2, Eye Irrit. 2, STO	T SE 3; H315 H319 H335	•			

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

Opecine oc	iic. Ellillits, it	i-lactors and ATE	
CAS No	EC No	Chemical name	Quantity
	Specific Cond	c. Limits, M-factors and ATE	
25513-64-8	247-063-2	2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine	25 - < 35 %
	oral: ATE = {	500 mg/kg	
1477-55-0	216-032-5	m-Phenylenebis(methylamine)	1 - < 8 %
	inhalation: LC50 = 3,89 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 2000 mg/kg; oral: LD50 = 930 mg/kg		
90-72-2	202-013-9	2,4,6-Tris(dimethylaminomethyl)phenol	5 - < 10 %
	dermal: LD5	0 = 1280 mg/kg; oral: LD50 = 2169 mg/kg	
104-15-4	203-180-0	p-Toluenesulphonic acid	1 - < 5 %
	STOT SE 3;	H335: >= 20 - 100	

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.





according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. B

Revision date: 29.11.2022 Page 3 of 13

Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

#### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

### After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

#### 4.2. Most important symptoms and effects, both acute and delayed

Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam

Extinguishing powder

Water spray jet

Carbon dioxide (CO2)

### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic

Carbon monoxide

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing.

#### Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

#### **General advice**

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

#### 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

### Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for





according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. B

Revision date: 29.11.2022 Page 4 of 13

taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

#### Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.

Wash hands thoroughly after handling. When using do not eat, drink or smoke.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed.

Store in a place accessible by authorized persons only.

Keep only in the original container in a cool, well-ventilated place.

## Hints on joint storage

Do not store together with: Oxidising agent, strong, Organic peroxides

Do not use for products which come into contact with the food stuffs.

#### Further information on storage conditions

Keep container tightly closed in a cool place.

storage temperature: 5 - 35°C

### 7.3. Specific end use(s)

see section 1.2

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters



according to UK REACH Regulation

# Multifix SE1000 Seismic, Comp. B

Revision date: 29.11.2022 Page 5 of 13

## **DNEL/DMEL values**

CAS No	Substance			
DNEL type	Cubotanico	Exposure route	Effect	Value
25513-64-8	2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine	<u> </u>	•	
Consumer D	NEL, long-term	oral	systemic	0,05 mg/kg bw/day
1477-55-0	m-Phenylenebis(methylamine)			
Worker DNE	L, long-term	inhalation	systemic	1,2 mg/m³
Worker DNE	L, long-term	inhalation	local	0,2 mg/m³
Worker DNEL, long-term		dermal	systemic	0,33 mg/kg bw/day
104-15-4	p-Toluenesulphonic acid			
Worker DNE	L, long-term	dermal	systemic	7,6 mg/kg bw/day
Worker DNE	L, long-term	inhalation	systemic	53,6 mg/m³
Consumer DNEL, long-term		dermal	systemic	2,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	8,7 mg/m³
Consumer DNEL, long-term		oral	systemic	0,05 mg/kg bw/day

## **PNEC** values

CAS No	Substance	
Environmenta	l compartment	Value
25513-64-8	2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine	
Freshwater		0,102 mg/l
Marine water		0,01 mg/l
Freshwater se	ediment	0,662 mg/kg
Marine sedim	ent	0,062 mg/kg
Micro-organis	ms in sewage treatment plants (STP)	72 mg/l
1477-55-0	m-Phenylenebis(methylamine)	
Freshwater		0,094 mg/l
Marine water		0,009 mg/l
Freshwater se	ediment	0,43 mg/kg
Marine sediment		0,043 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil 0,045 mg.		0,045 mg/kg
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol	
Freshwater		0,084 mg/l
Marine water		0,0084 mg/l
Micro-organis	ms in sewage treatment plants (STP)	0,2 mg/l
104-15-4	p-Toluenesulphonic acid	
Freshwater 0		0,073 mg/l
Marine water 0,0		0,0073 mg/l
Freshwater sediment 0,0577 m		0,0577 mg/kg
Marine sediment 0,00577 m		
Soil		0,016 mg/kg



according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. B

Revision date: 29.11.2022 Page 6 of 13

#### Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

#### 8.2. Exposure controls







## Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear eye/face protection. Wear safety glasses.

#### Hand protection

Recommended material: NBR (Nitrile rubber)

Breakthrough time: > 480 min

Thickness of the glove material: 0,7 mm

DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Wear suitable protective clothing.

## Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: solid (pasty)
Colour: grey / red
Odour: characteristic
Odour threshold: No data available

#### Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

not determined

not determined

boiling range:

Flash point: not applicable

**Flammability** 

Solid/liquid: not determined
Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

Self-ignition temperature

Solid: not determined



according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. B

Revision date: 29.11.2022 Page 7 of 13

Gas: not applicable
Decomposition temperature: not determined
pH-Value: not determined
Water solubility: The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Density (at 20 °C):

Relative vapour density:

not determined

1,42 g/cm³

not determined

#### 9.2. Other information

## Information with regard to physical hazard classes

Oxidizing properties Not oxidising.

### Other safety characteristics

Solid content: not determined Evaporation rate: not determined

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

see section 10.3

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent

### 10.4. Conditions to avoid

see section 7.2

## 10.5. Incompatible materials

Oxidising agent, strong

#### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in GB CLP Regulation

### **Acute toxicity**

Harmful if swallowed.

#### **ATEmix** calculated

ATE (oral) 1051,3 mg/kg; ATE (inhalation vapour) 107,60 mg/l; ATE (inhalation dust/mist) 15,100 mg/l



according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. B

Revision date: 29.11.2022 Page 8 of 13

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
25513-64-8	2,2,4(or 2,4,4)-Trimeth	ylhexane-1	,6-diamine			
	oral	ATE mg/kg	500			
1477-55-0	m-Phenylenebis(methy	lamine)				
	oral	LD50 mg/kg	930	Rat		
	dermal	LD50 mg/kg	2000	Rabbit		
	inhalation (1 h) vapour	LC50	3,89 mg/l	Rat		
	inhalation dust/mist	ATE	1,5 mg/l			
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol					
	oral	LD50 mg/kg	2169	Rat		
	dermal	LD50 mg/kg	1280	Rat		

### Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

### Sensitising effects

May cause an allergic skin reaction. (2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine; m-Phenylenebis(methylamine))

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

### **Further information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

The product is not: Ecotoxic.



according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. B

Revision date: 29.11.2022 Page 9 of 13

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
25513-64-8	2,2,4(or 2,4,4)-Trimet	2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine						
	Acute algae toxicity	ErC50 mg/l	43,5	72 h	Selenastrum capricornutum		OECD 201	
	Fish toxicity	NOEC mg/l	10,9	30 d	Danio rerio (zebrafish)		OECD 210	
	Crustacea toxicity	NOEC mg/l	1,02	21 d	Daphnia magna (Big water flea)		OECD 211	
1477-55-0	m-Phenylenebis(meth	ylamine)						
	Acute fish toxicity	LC50 mg/l	87,6	96 h	Oryzias latipes (Ricefish)		OECD 203	
	Acute algae toxicity	ErC50 mg/l	32,1	72 h	Selenastrum capricornutum		OECD 201	
	Acute crustacea toxicity	EC50 mg/l	15,2	48 h	Daphnia magna (Big water flea)		OECD 202	
	Crustacea toxicity	NOEC	4,7 mg/l	21 d	Daphnia magna (Big water flea)		OECD 211	
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol							
	Acute fish toxicity	LC50	175 mg/l	96 h	Cyprinus carpio (Common Carp)			
	Acute algae toxicity	ErC50	84 mg/l	72 h	Desmodesmus subspicatus		OECD 201	
	Algae toxicity	NOEC mg/l	6,25	3 d				

## 12.2. Persistence and degradability

The product has not been tested.

	roduct has het been teeted.				
CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
25513-64-8	2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine				
		7 %	28		

## 12.3. Bioaccumulative potential

The product has not been tested.

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
25513-64-8	2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine	-0,3
1477-55-0	m-Phenylenebis(methylamine)	0,18
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol	0,219
104-15-4	p-Toluenesulphonic acid	0,93

#### **BCF**

CAS No	Chemical name	BCF	Species	Source
1477-55-0	m-Phenylenebis(methylamine)	2,69		

## 12.4. Mobility in soil

The product has not been tested.

## 12.5. Results of PBT and vPvB assessment



according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. B

Revision date: 29.11.2022 Page 10 of 13

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No information available

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

#### **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

#### Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

### List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND

PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

## List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste): packaging containing residues of or contaminated by

hazardous substances; hazardous waste

### **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1. UN number or ID number: UN 3259

**14.2. UN proper shipping name:** AMINES, SOLID, CORROSIVE, N.O.S. (2,2,4(or 2,4,4)

-Trimethylhexane-1,6-diamine; m-Phenylenebis(methylamine))

14.3. Transport hazard class(es): 8

14.4. Packing group:

Hazard label: 8



Classification code: C8
Special Provisions: 274
Limited quantity: 1 kg
Excepted quantity: E2
Transport category: 2



according to UK REACH Regulation

Multifix SE1000 Seismic, Comp. B

Revision date: 29.11.2022 Page 11 of 13

Hazard No: 80 Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3259

**14.2. UN proper shipping name:** AMINES, SOLID, CORROSIVE, N.O.S. (2,2,4(or 2,4,4)

-Trimethylhexane-1,6-diamine; m-Phenylenebis(methylamine))

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Classification code: C8
Special Provisions: 274
Limited quantity: 1 kg
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 3259

**14.2. UN proper shipping name:** AMINES, SOLID, CORROSIVE, N.O.S. (2,2,4(or 2,4,4)

-trimethylhexane-1,6-diamine; m-Phenylenebis(methylamine))

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Special Provisions: 274
Limited quantity: 1 kg
Excepted quantity: E2
EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3259

**14.2. UN proper shipping name:** AMINES, SOLID, CORROSIVE, N.O.S. (2,2,4(or 2,4,4)

-trimethylhexane-1,6-diamine; m-Phenylenebis(methylamine))

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3 A803

5 kg

Y844

Excepted quantity:

E2

IATA-packing instructions - Passenger:859IATA-max. quantity - Passenger:15 kgIATA-packing instructions - Cargo:863IATA-max. quantity - Cargo:50 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No





according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. B

Revision date: 29.11.2022 Page 12 of 13

#### 14.6. Special precautions for user

No information available.

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

#### Additional information

VOC content: 21,7 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

#### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the

'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**

#### Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

BCF: Bioconcentration factor

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level

DNEL: Derived No Effect Level

EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

ICAO: International Civil Aviation Organization

IC50: Inhibitory concentration, 50%

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Oragnisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic

vPvB: very persistent and very bioaccumulative

PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals



according to UK REACH Regulation

## Multifix SE1000 Seismic, Comp. B

Revision date: 29.11.2022 Page 13 of 13

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Acute Tox. 4: Acute toxicity, Category 4

Aguatic Chronic 3: Long-term aguatic hazard, Category 3 Eye Dam. 1: Serious eye damage/eye irritation, Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2 Skin Corr. 1B: Skin corrosion/irritation, Category 1B

Skin Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1: Skin sensitilization, Category 1

## Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method

#### Relevant H and EUH statements (number and full text)

	,
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)